



S MATIÈRES
MARIUS AURENTI



Material – 01.03.10

Ma's gloss lacquer



Paint

Definition

Glossy lacquer paint in aqueous phase (based on urethane alkyd resin) for interior and exterior decoration.

Properties

Resistant to aggression and scratching. Low VOC content. Easy to spread and stable gloss. Easy maintenance. Fast drying.

Application

Apply an appropriate undercoat for the type of substrate (for example, Marius Aurenti white wall acrylic primer). Stir the product thoroughly to make it uniform before and during application. Apply two coats using a lacquer roller or acrylic brush. Sanding between coats with a wet abrasive is strongly recommended. The product is ready to use. Possibility of diluting with up to 5% water if necessary. Ma's lacquer must be applied, not spread.

Clean the equipment with warm water immediately after use. Application conditions in compliance with French standard NF P 74-201 (DTU 59.1). Ambient and substrate temperature above 8°C and below 35°C

Substrates

Application to new or old well-prepared substrates. Mineral, wood and even metal substrates. New substrates must be sound, clean, and dry (refer to French standard NF P 74-201 / DTU 59.1 or equivalent local standard). Old substrates must be clean and free of paint flakes. They must be analysed in advance to determine the priming coat. Preparation must be performed according to standard practice.

Appearance

High gloss

Yield

12 to 14m² per litre and per coat, according to substrate

Drying

3 h and re-coverable after 24 h (at 20°C and 50% RH)

Maintenance

Washable

Dry extract

39% by volume; 52% by weight

VOC

Maximum 99 g/L (EU 2010 limit: 100 g/L)

Shelf life

12 months (unopened)

Packaging

1, 2.5, 5, 10, and 15 l

Colours

Marius Aurenti colour chart

Classification

AFNOR NF T 36005

Family I Class 4a