

MARIUS AURENTI



ITP TERRACE & POOL IMPREGNATION

Finishes

AREAS OF USE Protection of exterior microcement floors and walls.	PROPERTIES Prevents the penetration of water and oily products, beading effect, facilitates maintenance, colorless, does not yellow.
COMPOSITION Solvent-based acrylic impregnation.	PACKAGING 5 L

Application

SUBSTRATE AND SUBSTRATE PREPARATION

Concretes and their derivatives are perfectly consistent. Clean raw concrete with an acidic cleaner suitable for new screeds and rinse to neutralize the pH. Sand the varnished concrete with 120 grit sandpaper to repair the wear layer.
--

APPLICATION EQUIPMENT

Short-pile roller, brush.

APPLICATION CONDITIONS

It is imperative to measure the ambient and substrate temperatures and the relative humidity of the ambient and substrate before any application of the product.
--

ROOM TEMPERATURE	>5°C and <30°C
SUBSTRATE TEMPERATURE	The substrate must be at a temperature of +3°C relative to the dew point in order to avoid any condensation phenomenon.
SUBSTRATE MOISTURE	<4% A damp substrate or the presence of moisture can cause the solvent-based oil-repellent impregnation to whiten.
RELATIVE HUMIDITY	<80%
Protect from wind, direct sunlight, rain, frost, and the surrounding flora and fauna during application and setting.	

Failure to comply with these application conditions may prevent the chemical reaction of ITP Terrace & Pool Impregnation. In this case, the impregnation will not achieve its specified chemical and mechanical performance. Whitening may also occur.
--

APPLICATION METHOD

Stir ITP Terrace & Pool Impregnation thoroughly before use.
Apply 2 coats. Excessive thickness may cause surface defects.

COVERAGE

200 to 300 g/m² for 2 coats, depending on substrate porosity.
Indicative coverage; actual consumption may vary according to application conditions and substrate porosity.

Excessive thickness of ITP Terrace & Pool Impregnation may cause bubbling or even delamination of the previous impregnation coats.

DRYING TIME AT 20°C AND 60% RELATIVE HUMIDITY:

DUST-FREE TIME	30 minutes
BETWEEN COATS	5 hours minimum; abrade the previous coat if more than 24 hours have elapsed.
COMPLETE DRYING	24 hours minimum

In the event of intervention by another trade on the site, we recommend using micro-breathable protective tarpaulins such as Landolt's Floorliner Vapor.

TOOL CLEANING

Solvent-based cleaner



PRODUCT APPEARANCE

APPEARANCE IN THE CONTAINER: CLEAR LIQUID

FINISHED APPEARANCE: TRANSPARENT, COLORLESS FILM WITH A SILKY MATTE TO SATIN FINISH. PLEASE NOTE THAT THE ORIGINAL COLOR MAY BE INTENSIFIED BY ONE OR TWO SHADES.

DENSITY (AT 20°C)
0.9

PRECAUTIONS FOR USE

ITP TERRACE & POOL IMPREGNATION IS DESIGNED TO PREVENT STAINING OF POROUS MATERIALS SUCH AS CONCRETE OR STONE. DESPITE THE HIGH PERFORMANCE OF MA'S TREATMENTS, THESE PROTECTIVE SYSTEMS MAY BE DAMAGED BY PROLONGED OR REPEATED EXPOSURE TO AGGRESSIVE SUBSTANCES.

DO NOT ALLOW WATER TO REMAIN STAGNANT ON TREATED SURFACES. THIS PROTECTION IS NOT DESIGNED TO PROVIDE WATERPROOFING (FOR EXAMPLE, BENEATH FLOWERPOTS, SPONGES, OR WET CLOTHS). AVOID PROLONGED OR PERMANENT CONTACT WITH AGGRESSIVE CHEMICALS SUCH AS ACIDS, BASES, VINEGAR, NAIL POLISH REMOVER, BLEACH, SOLVENTS, AND HAND SANITIZER.

SPLASHES OF HAND SANITIZER ON THE IMPREGNATED SURFACE MAY CAUSE IRREVERSIBLE DAMAGE. THOROUGHLY PROTECT ANY SURFACES THAT MAY BE EXPOSED TO IT.

STORAGE

1 YEAR IN THE ORIGINAL UNOPENED PACKAGING, PROTECTED FROM SUNLIGHT AND FROST, AT A TEMPERATURE BETWEEN +5°C AND 35°C.
CHECK THE PRODUCT'S BEST-BEFORE DATE ON THE PACKAGING.

SAFETY

WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. FOR FURTHER SAFETY INFORMATION, REFER TO THE SAFETY DATA SHEET. VOC CONTENT IS ALSO PROVIDED IN SECTION 15 OF THE SAFETY DATA SHEET.



MARIUS AURENTI

For 40 years, Marius Aurenti has been innovating to improve the performance of decorative materials and the sensations they provide.

A mineral and plant aesthetic, close to Nature, to which our works pay homage and for which our environmental commitment is total.

MA's is also present, through its training and support, alongside quality French craftsmanship which, every day in our workshops as well as in the field, strives to make each place unique, beautiful and timeless.



www.mariusaurenti.com +33 (0)9 87 87 65 75