

MARIUS AURENTI



WALL PROTECTIVE VARNISH

Finishes

AREAS OF APPLICATION:

Protection and decoration of interior walls

COMPOSITION :

One-component, water-based varnish

PROPERTIES :

Transparent, non-yellowing, good adhesion, quick drying, odorless.

PACKAGING:

1 kg and 5kg



SUBSTRATE AND SUBSTRATE PREPARATION

Concrete and concrete-based substrates must be perfectly sound, clean and dry. For repairs, sand varnished concrete with 120-grit sandpaper.

CONSUMPTION

Indicative value that may vary depending on application conditions and substrate porosity.
75 g/m² for 1 coat

DILUTION

None

APPLICATION EQUIPMENT

Lacquer roller. The equipment must be perfectly dry and clean.

APPLICATION METHOD

Shake the product well before application.
To avoid roller marks, it is advisable to always work wet-on-wet.

APPLICATION CONDITIONS

TEMPERATURE	>10°C and <35°C (ideal temperature: >15°C and <20°C)
RELATIVE HUMIDITY	<80%
SUBSTRATE MOISTURE CONTENT	4% maximum

DRYING TIME AT 20°C AND 60% RELATIVE HUMIDITY

DRY TO THE TOUCH	30 minutes
RECOATABLE	After a minimum of 4 hours and a maximum of 8 days. Beyond that, light sanding is necessary.
READY FOR CAREFUL USE	Minimum 24 hours
FULL HARDNESS	Minimum 4 days

TOOL CLEANING

Clean the tools with water immediately after use.

PRODUCT APPEARANCE

Colorless, viscous liquid

DRY FILM APPEARANCE

Transparent, silky matte film

DENSITY (AT 20°C)

1

SPECULAR GLOSS UNDER 60°

Silky matte: approximately 6 GU. These figures are indicative and may vary depending on application conditions.

PRECAUTIONS FOR USE

The varnish helps prevent staining of porous materials such as concrete or stone. Despite the high performance and qualifications of MA's treatments, prolonged and repeated exposure may damage the material.

Avoid prolonged or permanent contact with aggressive chemicals such as acids, bases, vinegar, bleach or solvents... These varnishes are not recommended for surfaces exposed to hot oils, such as kitchen splashbacks.


Wall Protective Varnish is intended exclusively for wall applications.

STORAGE AND SAFETY

1 year in its original packaging, protected from sunlight and frost in a cool, well-ventilated place.

Check the best-before date on the packaging before use.

For further safety information, please refer to the Safety Data Sheet. VOC content is also available in Section 15 of the Safety Data Sheet.



MARIUS AURENTI

For 40 years, Marius Aurenti has been innovating to improve the performance of decorative materials and the sensations they provide.

A mineral and plant aesthetic, close to Nature, to which our works pay homage and for which our environmental commitment is total.

MA's is also present, through its training and support, alongside quality French craftsmanship which, every day in our workshops as well as in the field, strives to make each place unique, beautiful and timeless.



www.mariusaurenti.com +33 (0)9 87 87 65 75